

## Patent Abstracts of Japan

PUBLICATION NUMBER : 2003106693  
PUBLICATION DATE : 09-04-03


APPLICATION DATE : 26-09-01  
APPLICATION NUMBER : 2001294206

APPLICANT : TOSHIBA CORP;

INVENTOR : KASHIMA KOJI;

INT.CL. : F25B 5/02 F25B 1/00 F25B 1/10  
F25B 5/04 F25D 21/04

TITLE : REFRIGERATOR



2: 2段圧縮コンプレッサ  
3: 凝縮器  
5: 冷蔵室用蒸発器  
9: 冷凍室用蒸発器  
37: 冷蔵サイクル

**ABSTRACT :** PROBLEM TO BE SOLVED: To prevent liquid return into a suction port on intermediate pressure side of a two-stage compression compressor and dew condensation in a suction pipe for a refrigerating chamber, when an excessive load is applied to a freezing chamber.

**SOLUTION:** A refrigerator according to this invention is provided with a refrigerating cycle 37 constituted by the two-stage compression compressor 2 having a suction port 2c on low pressure side and the suction port 2b on intermediate pressure side, a condenser 3, an evaporator 5 for the refrigerating chamber, and an evaporator 9 for the freezing chamber to exchange heat of refrigerant coming out of the evaporator 5 for the refrigerating chamber and refrigerant coming out of the evaporator 9 for the freezing chamber. According to this configuration, refrigerant density at the suction port 2c on low pressure side of the two step compressor 2 is increased, refrigerant flow rate of the evaporator 9 for the freezing chamber is increased, and liquid return into the suction port 2b on intermediate pressure side and dew condensation in the suction pipe 7 for the refrigerating chamber is prevented.

COPYRIGHT: (C)2003,JPO